

TCE Group Srl - EVO Series Data Sheet

Model	Volt (V)	Amp (A)	Weight (KG)	Capacity Ah		Input Vac		Box
				10h	12h	380-440 Vac	220-255 Vac	
						Amp (A)	Amp (A)	
EVO24060	24	60 A	24	300	380	3	/	E
EVO24080		80 A	55	420	540	4	12	E
EVO24100		100 A	58	520	680	5	17	E
EVO24120		120 A	59	600	800	6	20	E
EVO24140		140 A	63	720	900	7	24	E
EVO24160		160 A	64	870	1000	8	27	E
EVO24180		180 A	75	900	1125	9	/	E

EVO36080	36	80 A	58	430	560	6	20	E
EVO36100		100 A	61	520	680	7	25	E
EVO36120		120 A	62	600	800	9	30	E
EVO36140		140 A	66	720	900	10	34	E
EVO36160		160 A	73	870	1000	12	39	E
EVO36180		180 A	88	900	1125	13	/	E

EVO48060	48	60 A	58	300	380	6	20	E
EVO48080		80 A	61	430	560	8	27	E
EVO48100		100 A	64	520	680	10	33	E
EVO48120		120 A	73	600	800	12	39	E
EVO48140		140 A	83	720	900	14	/	E
EVO48160		160 A	88	870	1000	16	/	E
EVO48180		180 A	95	900	1125	22	/	E
EVO48200		200 A	100	1100	1250	28	/	E

EVO72080	72	80 A	72	430	560	12	26	E
EVO72100		100 A	85	520	680	15	32	E
EVO72120		120 A	90	600	800	18	39	E

EVO80080	80	80 A	65	430	560	13	42	E
EVO80100		100 A	72	520	680	16	54	E
EVO80120		120 A	81	600	800	19	/	E
EVO80140		140 A	90	720	900	23	/	E
EVO80160		160 A	97	870	1000	27	/	B
EVO80180		180 A	\	900	1125	34	/	B
EVO80200		200 A	\	1100	1250	39	/	B

Notes

- All the models are supplied with SHUNT
- Under request it is possible to use the metal front panel instead of the standard ABS one
- The mentioned charging capacity may change based on many variable factors (temperature, mains voltage network, power transformer connections, battery status, ...)

Box "E"

Dimensions: 400 x 600 x 900(H)



acubat.es