

TCE Group Srl - NEOS Series Data Sheet

Model	Volt (V)	Amp (A)	Input Vac		Battery Capacity			Module
			Amp (A)	Vac	8h	10h	12h	
ONR1210	12 V	10 A	2	95-265 Vac	60	80	100	0
N1210		10 A	2	180 - 265Vac	60	80	100	1
N1215		15 A	2		90	120	150	1
ON1215		15 A	2		90	120	150	1
N1220		20 A	2		120	160	200	1
ON1220		20 A	2		120	160	200	1
N1225		25 A	2		150	200	250	2
ON1225		25 A	2		150	200	250	2
ONR2410	24 V	10 A	2		95-265 Vac	60	80	100
N2410		10 A	2	180 - 265Vac	60	80	100	0
N2415		15 A	2		90	120	150	1
ON2415		15 A	2		90	120	150	1
N2420		20 A	3		120	160	200	1
ON2420		20 A	3		120	160	200	1
N2425		25 A	3		150	200	250	2
ON2425		25 A	3		150	200	250	2
N2430		30 A	4		180	240	300	3
ON2430		30 A	4		180	240	300	3
N2435		35 A	4		210	280	350	4
ON2435		35 A	4		210	280	350	4
N2440		40 A	5		240	320	400	4
ON2440		40 A	5		240	320	400	4
N2450		50 A	6		300	400	500	4
ON2450		50 A	6		300	400	500	4
N3610	36 V	10 A	2		180 - 265Vac	60	80	100
ON3610		10 A	2	60		80	100	2
N3615		15 A	2	90		120	150	2
ON3615		15 A	2	90		120	150	2
N3620		20 A	4	120		160	200	2
ON3620		20 A	4	120		160	200	2
N3625		25 A	5	150		200	250	2
ON3625		25 A	5	150		200	250	2
N3630		30 A	6	180		240	300	3
ON3630		30 A	6	180		240	300	3
ON3650		50 A	9	300		400	500	5
N3650		50 A	9	300		400	500	5
N4810	48 V	10 A	3	180 - 265Vac	60	80	100	2
ON4810		10 A	3		60	80	100	2
N4815		15 A	4		90	120	150	2
ON4815		15 A	4		90	120	150	2
N4820		20 A	6		120	160	200	2
ON4820		20 A	6		120	160	200	2
N4825		25 A	8		150	200	250	2
ON4825		25 A	8		150	200	250	2
N4830		30 A	8		180	240	300	4
ON4830		30 A	8		180	240	300	4

N4835		35 A	10		210	280	350	4		
ON4835		35 A	10		210	280	350	4		
N4840		40 A	10		240	320	400	5		
ON4840		40 A	10		240	320	400	5		
N4850		50 A	12		300	400	500	5		
ON4850		50 A	12		300	400	500	5		
N4870		70 A	14	400 Vac	450	560	750	7		
72 V										
N7210	72 V	10 A	4	180 - 265Vac	60	100	120	2		
ON7210		10 A	4		60	100	120	2		
N7215		15 A	6		90	120	150	2		
ON7215		15 A	6		90	120	150	2		
N7220		20 A	8		120	160	200	3		
ON7220		20 A	8		120	160	200	3		
N7225		25 A	8		150	200	250	4		
ON7225		25 A	8		150	200	250	4		
N7230		30 A	11		180	240	300	6		
ON7230		30 A	11		180	240	300	6		
N7235		35 A	13		210	350	420	6		
ON7235		35 A	13		210	350	420	6		
80 V										
ON8022		80 V	22 A		10	180 - 265 Vac	130	180	220	4

Note

- The charging capacity above mentioned may change based on many different variables
- Versions available in 110Vac under request

CODE GUIDE

- **ONR** Charger with the possibility to change charging curve with infrared
- **ON** Charger with accessories for on-board installation
- **N** Charger without any accessory